



Prepared for: Pleasant Valley
 Good Through: 10-31-2026
 Dealer Representative: Jared Kreger
 Representative Email: jaredk@frontier.com
 Representative Phone: 610-366-2095 Ext. 3

Model #	MSRP
MF2M.60 Hydro Tractor	\$ 64,031.00
- MF2M.60 Hydro Tractor - MF2M.60 - HST Deluxe Cab - F27x10.50-15 R44x18.00-20 - FL2814 SS Loader - No Bucket 72" High Volume SS Bucket - NA Assy Pkg - Deluxe Cab	- EN Operator's Manual -2M.50/ - EN OM - FL2611/FL2814/FL2815
Total Retail Price	\$ 64,031.00
<i>Additional Sale Price Items (See Page 2)</i>	\$ 1,350.00

Cash Price
\$55,150.00

Cash Price	Cash Price	
	Sale Price	\$ 55,150.00
	Trade-In:	\$ 0.00
	Net Price	\$ 55,150.00
	Taxes	\$ 0.00
	Final Customer Price	\$ 55,150.00

**5 YEAR
POWERTRAIN
WARRANTY**

**AGCO
PARTS**
GENUINE PARTS
& SERVICE

**AGCO
PROTECTION**
ASK ABOUT
EXTENDED
COVERAGE

This Letter is a non-binding indication of interest regarding a possible transaction on the general terms and conditions outlined herein and is not a legal commitment. This Letter is intended for the use of the Customer only. *The following is a proposal for financing for the customer named herein ("Customer") regarding the equipment described herein ("Equipment") by AGCO Finance LLC for discussion purposes only. Customer participation subject to credit qualification and approval by AGCO Finance LLC. Not all Customers may qualify for this rate or term. This proposal is not a statement of all terms and conditions of any financing that may be approved. This Letter is intended for the use of the Customer only. This Letter is valid until "Good Through" date listed above and thereafter shall automatically be deemed to be null and void. ***The cash price is a good faith dealer estimate only. See dealer for details.





Prepared for: Pleasant Valley
Good Through: 10-31-2026
Dealer Representative: Jared Kreger
Representative Email: jaredk@frontier.com
Representative Phone: 610-366-2095 Ext. 3

Additional Sale Price Items

72" Bolt-on Cutting Edge	\$	550.00
Loaded Rear Tires With Rim-guard	\$	800.00
	\$	NaN
	\$	NaN
	\$	NaN
Total	\$	1,350.00

2M.60

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Engine:
 - 60.3 Gross HP Iseki 4-Cylinder Liquid Cooled Diesel, 2.43 L Direct Injection, Turbocharged and Intercooled, Electronic Engine Control
 - 47.0 PTO HP @ 2600 RPM - Shuttle
 - 44.6 PTO HP @ 2600 RPM - Hydrostatic
 - Emission Standard Category: Tier 4F
 - Exhaust Gas Recirculation (EGR)
 - Diesel Oxidation Catalyst (DOC)
 - Regenerating Diesel Particulate Filter (DPF)
- Dual Element Dry Type Air Cleaner
- Transmission
 - 12Fx12R Power Shuttle with 4 Synchronized Gears and 3 Ranges
- Servo-HST Electronic Hydrostatic Transmission with 3 Ranges, Cruise Control, Stall Guard, Max Speed Control and Response Control
- Sealed Wet Disc Brakes
- Pedal Operated Differential Lock
- PTO:
 - Rear - 540 RPM Independent Electro Hydraulic
 - Mid - Optional 2023 RPM Independent for HST

HYDRAULIC SYSTEM

- 3-Point Hitch Cat I & II with Position Control Standard, Draft Control Standard on Models Equipped with Mechanical Transmission
- Lift Capacity @ 24 inches - 3,307 lb (1500 kg) for Shuttle
- Lift Capacity @ 24 inches - 3,086 lb (1400 kg) for HST
- Telescopic Stabilizers
- Telescopic Draft Link Ends
- Dual Engine Driven Gear Pumps
- Flow at Remotes 12.7 GPM (48.0 LPM) for Shuttle and 12.6 GPM (47.8 LPM) for HST
- Hydrostatic Power Steering
- One Rear Remote Valve Standard on Cab Models, up to 3 Possible. Loader Joystick Standard

INSTRUMENTS

- Combination Digital and Analog Front Dash Display
- Tachometer and Hour Meter
- Temperature and Fuel Gauges
- 4wd Engagement Indicator
- Warning Lights: High Beam Indicator, Engine Oil Pressure, PTO Engagement, Battery Charge (alt) Indicator, Glow Plug Indicator and Flasher Indicators
- Key Operated Electronic Fuel Shutoff and Glow Plug Control

OTHER STANDARD FEATURES

- ISO Mounted Flat Platform w/Molded Rubber Floor Mat
- One Piece Tilt-up Hood
- 3 Position Tilt Steering
- Premium Adjustable Suspension Seat with Arm Rest
- 2 Post Folding ROPS and Retractable Seat Belt
- Turn Signals, Flashers, Tail Lights and SMV Emblem
- 4 Headlights
- Back up Alarm Ready

CAB FEATURES

- Heating and Air Conditioning
 - Mobile Phone Holder
 - Speakers, Radio Ready
 - Radio Antenna
 - Front and Rear Wiper / Washer
 - 2 Front Work Lights
 - 2 Rear Work Lights
 - Rear and Side opening Windows
 - Right and Left Entry Doors
 - Right and Left External Mirrors
 - Premium Digital Display with Ground Speed, Engine Coolant, Temperature, Fuel Level and Diagnostic Readout
 - 12V Power Outlet
 - ROPS Certified
 - Recirculation Filter
- **Note: 3-Point Mounted Backhoe Installation Voids Warranty. Use the Required Subframe Mounting Kit.**

IMPLEMENT FEATURES

FL2814 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.76 inch Double Acting Lift Cylinders
- (2) 2.56 inch Double Acting Bucket Cylinders
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- 3rd Function Capable, Soft-Drive Capable
- Galvanized Steel Bushings with Recessed Grease Points
- Universal Skid Steer Implement Attachment
- Grille Guard Standard

- Fits 2M.50 and 2M.60 Compact Tractor Models
- Maximum Lift Height at Pivot Pins: 111 Inches
- Lift Capacity to Full Height at Pivot Pins: 2,570 lbs
- Lift Capacity 19.5" Forward of Pins: 1,880 lbs
- Breakout Force at Pivot Pins: 3,910 lbs
- Rated Hydraulic Pressure: 2,277 PSI
- Maximum Roll Back Angle: 26 Degrees
- Dump Angle: 54 Degrees

OCTOBER 2026